

RIEZLER

Pan and tilt camera

RSK-60

Article-No. 5-0033-001 (PAL)

Article-No. 5-0033-002 (NTSC)



Technical data

Application area	DN 70 - DN 300
Suitable for 87° bends	from DN 100
Swivel range	± 115°
Rotation range	infinite
Push operation	✓
Crawler operation	✓
Waterproof	✓ up to 5 bar
Lighting	18 LEDs
Lens	68°
Zoom	✗
Focus	manual (1cm - ∞ 0.4 in - ∞)
High-resolution color camera module	420 lines
Image sensor	1/4" Color-CMOS
Upright picture	automatic horizont compensation
Parallel laser	✓
Distance laser points	30 mm 1.18 in
Internal pressure-supervision	✓
Pan / rotation angle	✓
Rotation angle vertical	✗
Pluggable mounting	✓
Operating temperature	0° to 60° C 32° to 140° F
Storage temperature	-10° to 60° C 14° to 140° F
Material	aluminium / stainless steel
Dimensions (Ø / Length)	60 / 100 mm 2.4 / 3.9 in
Weight	ca. 680 g 1.5 lbs

Address: 15, Jalan 8/23A, Taman Danau Kota, Setapak,
53300 Kuala Lumpur.

Email: sales@vinten-solutions.com

Phone : (6012) 316 1605

FAX : (603) 4131 2459

WhatsApp : <https://wasap.my/60123161605>

RIEZLER Inspektionssysteme GmbH & Co. KG

Sportplatzweg 5 | 87471 Durach | Germany
Tel. +49 (831) 27714 | info@riezler.eu | www.riezler.eu