Videoscope system

PRM280

Mitcorp

PRM100



PR Series Rugged and Robust **KEY FEATURES**

- · Capacitive touch technology for best performance and durability
- 7" TFT LCD
- 1m drop resistence
- 🕴 Sharp, clear, bright images
- 800x480 display resolution
- 640x480 video/photo resolution
- Rechargeable Li-battery
- Skype communication ready
- LED backlight function keys: ideal for dark environment operation
- USB camera: Support webcam device to remote access for data sharing and real-time diagnose
- USB reader: Simply connect to your PC to retrieve your data from the SD card, card reader is not necessary

Description

- Neck/Hand strap: convenience and great for operation
- Light weight: only 1.3kg





SPECIFICATIONS

X1000 PLUS SYSTEM

Features

• LCD

Snapshot

- Recording
- Dimensions
- System weight
- Dust & Water proof
- Drop resistence
- Battery
- Working temperature
- Storage temperature
- Charging temperature
- Relative humidity
- * Char
- Storage
- AV output
 Audio input
- Brightness Adjust
- 7[°]LCD (800 x 480) 640 * 480, jpeg 640 * 480, MPEG4 (with audio) 240 * 154 * 47mm 1.3kg (2.86 lb) IP57 1m Rechargeable Li-Battery 0~60 °C 0~60 °C 10~60 °C Max 95%, non condensing

Mass storage mode / Webcam mode

SD card, up to 32G

Built-in microphone

10.0mm (w/o mirror) 10.5mm (w/ side view mirror)

8 levels (5+3 Boost levels)

NTSC / PAL



PRM100 PIPE INSPECTION CAMERA

Features

Description

15m

Probing head diameter

- Tube length
- LED
- Buttons (on meter)
- Power m/ft switch LED backlight

Front / Side



PR series Rugged and Robust

- Eqipped with IP57 main system (F1000), great for • indoor and out door inspection
- Stainless steel camera head, IP 68 protection •
- Water and dust proof (camera head IP68, reel IP65) •
- Optional accessories: metal ring, brush, wagon •
- IP55 protection m/ft meter (optional) •









Accessories Metal ring ø50mm



Large Brush ø100mm or ø150mm





Wagon ø150mm ~300mm











Specifications		
Camera head:		
Lighting	8 LEDs (white)	
Dimeter / Lenth	28mm	
Material	Stainless steel	
Working temperature	-10°C - 60°C	
Storage temperature	-10℃ - 60℃	
Water proof	IP68 (10m)	
Display resolution	640 x 480	
Reel:		
Diameter	300mm	
Water proof	IP65	
Probe:		
Diameter	6.0mm	
Applicable pipe(ø)	40mm - 100mm	
Length	22mm	
Flexibility	Four 90° bends in 40mm pipe	