## TORMIN

# BC5401J LED Explosion Proof Emergency Light





Ex mark: Ex de op is IIC T5 Gb Ex op is tb IIIC T95℃ Db, IP66

#### Characteristics

- It is made using a special aluminum housing, anti-corrosion performance than 304 stainless steel, suitable for long-term highly corrosive environment of offshore platforms, chlor-alkali, hydrogen sulfide, etc.
- The anti corrosion, abrasion proof, power coated cover which is dust proof, water proof, make the lamp an excellent option for all kinds of high environment.
- All 304 stainless steel bracket screw (customizable 316), can effectively guarantee the long-term strength and strong corrosion problems of lamps.
- Terminals are provided at both ends, can be directly wired in parallel, eliminating the junction box and installation costs.
- A variety of installation as optional: ceiling, oil derrick, the side walls, curved rods, boom, etc.


#### **Application**

- It can be widely used in petrochemical plants, oil platforms, oil pump housing, transit stations and other flammable and explosive places as fixed lighting.
- Gas explosive environment: Group IIA, IIB, IIC.
- Zone1, Zone2; Zone21, Zone22

#### **Main Specification**

Item	Technical Parameters		
Rated wattage (W)	2×20W 2×10W		
Emergency wattage (W)	20W	10W	
Input voltage (V)	90~26	64VAC	
Rated frequency	50Hz	/ 60Hz	
Light source	LE	ED	
Light efficiency (Im/W)	9	0	
CRI	8	0	
Life time (h)	50,	000	
CCT	5000K		
Emergency duration (min)	90	180	
Time of charging (h)	(	3	
Rated capacity	2.6Ah	/14.8V	
Leading-in cable diameter	ф 10mm-	- φ 14mm	
Cable entry	G3/4",M25×	1.5,NPT3/4"	
	(2×20W) 1390×180×110		
Dimension (mm)	(2×10W) 780×180×110		
(Emergency box) 230×220×105		) 230×220×105	
Net weight (kg)	10.7	6.6	
ivet weight (kg)	(Emergency box) 2.8		

#### **Light Distribution Curve**




Space Height Ratio: 1.5

## BC5401J LED Explosion Proof Emergency Light



### **Drawing of Dimension (Dimensions in mm)**

#### **Ceiling mounting**



BXP01 Explosion-Proof Emergency Box

#### Lamps ordering information

Order No.	Installation	Emergency wattage	Emergency duration
BC5401J-L2×10	coiling	10W	180min
BC5401J-L2×20	ceiling	20W	90min


#### Fitting ordering information (Standard)


Order No.	No.	Specification	Quantity
1	Ceiling Bracket	2	
P01	2	M8 Inner six angle bolt	4


#### Emergency box ordering information (Standard)

Order No.	No.	Specification	Quantity
BXP01	3	Explosion-Proof Emergency Box	1
BAPUI	4	Bracket	1

#### **Derrick installation**







BXP01 Explosion-Proof Emergency Box

#### Lamps ordering information

Order No.	Installation	Emergency wattage	Emergency duration
BC5401J-L2×10	Derrick type	10W	180min
BC5401J-L2×20	Demok type	20W	90min

#### Fitting ordering information (Optional)


Order No.	No.	Specification	Quantity
P02	1	Derrick bracket	2
	2	Base	2
	3	M8 Inner six angle bolt	4
	4	M24 screw	2

#### Emergency box ordering information (Standard)

Order No.	No.	Specification	Quantity
BXP01	3	Explosion-Proof Emergency Box	1
BAPUI	4	Bracket	1




#### Side wall mounting




BXP01 Explosion-Proof Emergency Box

#### **Rod mounting**



BXP01 Explosion-Proof Emergency Box

#### Pole mounting



#### Lamps ordering information

Order No.	Installation	Emergency wattage	Emergency duration
BC5401J-L2×10	Sidewall	10W	180min
BC5401J-L2×20		20W	90min

#### Fitting ordering information (Optional)

Order No.	No.	Specification	Quantity
DOS	1	Side wall bracket	2
P03	2	M10 Inner six angle bolt	4

#### Emergency box ordering information (Standard)

Order No.	No.	Specification	Quantity
BXP01	3	Explosion-proof emergency box	1
BAPUT	4	Bracket	1

#### Lamps ordering information

Order No.	Installation	Emergency wattage	Emergency duration
BC5401J-L2×10	Rod	10W	180min
BC5401J-L2×20	Nou	20W	90min

#### Fitting ordering information (Optional)

Order No.	No.	Specifications Model	Quantity
	1	Upper hoop	2
P04	2	Under hoop	2
P04	3	Dn32 Poles	1
	4	U tube clip	2
BXP01	5	Explosion-Proof Emergency Box	1
DAPUT	6	Bracket	1

#### Lamps ordering information

Order No.	Installation	Emergency wattage	Emergency duration
BC5401J-L2×10	Pole	10W	180min
BC5401J-L2×20	Pole	20W	90min

#### Fitting Ordering Information (Optional)

Order No.	No.	Specification	Quantity
P05	1	Pole mounting bracket	1
	2	19cm Screw(M8)	1
P02	3	Connector G3/4" male- male	1
BXP01	4	Explosion-proof emergency box	1