



Ex marking: Ex de IIC T6 Gb

### Application

This product is suitable for construction work, accident rescue, line, equipment inspection, maintenance and various flammable and explosive places as mobile lighting



### Characteristics

- The dual modes of spot and flood light can be switched freely. When the lamp is working, it will switch with the switch for 3 seconds;
- The bottom of the lamp has a strong adsorption function, which can be easily adsorbed on all kinds of pipe, and can also be adsorbed on category cabinets. The adsorption force is much higher than similar products.
- The irradiation angle can be adjusted arbitrarily within the range of 135 degrees.
- CREE light source, strong light power of 13 watts;
- Stainless steel 304 externally coated silicon rubber handle, which will not hurt your hands for many years;
- Protection level reaches IP66, which can effectively resist strong rainstorm;
- When the lamp is off, long press for two seconds to automatically detect the power, flash 5 times for full power, flash 4 times for 80% power, and so on.

### Main Specification


Specification	Unit	Spot / Flood value	
Wattage of light source	W	13	
Rated voltage	V	33.3	
Rated capacity	mAh	2600	
Luminous flux	High	lm	1500
	Low	lm	900
Discharge time	High	h	9
	Low	h	16
Recharge time	h	≥6	
Service life of battery	times	≈1000	
Overall dimension	mm	151×131×272	
Net weight	Kg	1.5	



Magnetic adsorption



Charger



LED light source(CREE)