

ZY8601S Series LED Light(Bracket)

TORMIN

IP
66
Ta
50
Ta
-40



Characteristics

- Unique 220° beam angle makes the light more even, reducing eyestrain to the operator.
- Adopts high efficient heat conduction material, heat dissipation system. It ensures the 50,000 hours LED life.
- World top brand LED, it can save more than 40% energy than metal halide lamp.
- World top brand LED driver, stable quality.
- Easy maintenance.
- It adopts special aluminum which anti corrosion performance is much better than 304 stainless steel, durable to be used in highly corrosive area.

Application

It is suitable for use in all kinds of workshop, storage room, power station, furnace etc.



Main Specification

Item	Technical Parameters
Input voltage (V)	90 ~ 264VAC 18-55VDC optional
Rated frequency	50Hz / 60Hz
Light source	LED
Life time (h)	50,000
CRI	Ra 70 (80 optional)
CCT	5000K(3000K/4000K optional)
Leading-in cable diameter	φ 8~ φ 14mm
Dimension (mm)	270×250×167mm
Net weight (kg)	3Kg

Ordering Reference

Model number	Picture	Rated wattage (W)	Light output (lm)	Space height ratio	Mounting height (m)	Light distribution curve(1000cd/lm)	Equivalent to
							MH
ZY8601S-L30-200°		30W	4020	1.75	/		70W
ZY8601S-L40-200°		40W	5240				100W
ZY8601S-L50-200°		50W	6470				100W
ZY8601S-L60-200°		60W	7390				150W

Drawing of dimension (Dimensions in mm)

